

SPECIFICATIONS

FIRE RATED DOORS

Size	Custom sizes available up to 1500mm wide x 3000mm high (single) & 3000mm wide x 3000mm high (double)
Fire Rating	Up to 60/90/120/240 min as per European / British & American Standards
Material	Cold Rolled Coil (CRC), Galvanized Steel (GI)
Leaf Steel Sheet Thickness	≥1.25mm
Frame Steel Sheet Thickness	≥1.50mm
Door Leaf Thickness	45-47mm
Core Construction	Steel Stiffened Rockwool or Honeycomb Core
Paint	Electrostatic Powder Coating Liquid Painting (Epoxy, DOKO & Oil Paint) Finish / Touch up paint applied at site
Frame Anchoring	Expansion Type (for masonry walls) Z-type (for dry walls) Other types available upon request
Frame Corner	Welded Knockdown
Frame Jamb Depth	From 100-500mm standard (150mm)
Door Construction	Interlocking / Welded
Handing	Right Hand (Inward or Outward) Left Hand (Inward or Outward)
Hardware	Must be fire rated Please contact for options
Compliance	Manufactured in accordance to BS 476 Part 22, EN 1634-1, NFPA 252, NFPA 257, UL 10(B), UL 10(C) and ASTM E2010 certified by Intertek
Optional	Fire Rated Automatic Louver (up to 610mm x 610mm) Vision Panel (Up to 500mm x 1000mm)

